

## PACKAGE OF ADDITIVES PA-2610

Specification BY 390401182.040-2019	Passenger car motor oil additive.		
Use recommendations	Treat rate*, % wt.		
SJ/CF/CF-4	2.5 % PA-2610 + 4.0 % PA-2600		
CF-4/SG	1.5 % PA-2610 + 4.0 % PA-2600 + 0.8 % CCK-400D		
SG/CD	1.6 % PA-2610 + 3.6 % PA-2600 <sup>1</sup>		
* - in combination with viscosity improver and pour point depressant 1- equivalent 5.2 % wt. PA-2615			
Some physical and chemical properties			
Characteristics	Minimum	Typical value	Maximum
Kinematic viscosity at 100 °C, mm <sup>2</sup> /sec. (cSt)	-	72.0	120.0
Flash point (COC), °C	180	210	-
Total base number (TBN), mg KOH/g	20.0	42.0	-
Nitrogen content, % wt.	-	1.15	-
Zinc content, % wt.	0.50	0.80	-
Sulfate ash content, % wt.	-	4.2	5.0
Condition of usage	Recommended solution temperature of package of additives in base oil is up to 70 °C. Any devices providing uniformity of stirring of package of additives in base oil can be used for dissolving. Shelf life at ambient temperature – 12 months.		
Safety requirements	Before usage the product please read material safety data sheet (MSDS) of the product.		