

PACKAGE OF ADDITIVES PA-4622

Quality requirements are established in production technology	Heavy duty diesel engine oil package of additives.		
Main benefits	Excellent protection against wear due to corrosion of bearing and cylinder liners. Excellent protection of engine valve train components. The highest level of prevention against damaging deposits common in high temperature modern diesel engines. Excellent control of soot.		
Use recommendations	Treat rate*, % wt.		
CI-4/SL	10.8 %		
CH-4/SJ	9.7 %		
* - in combination with viscosity improver and pour point depressant			
Some physical and chemical properties			
Characteristics	Minimum	Typical value	Maximum
Kinematic viscosity at 100 °C, mm ² /sec. (cSt)	150.0	210	230.0
Flash point (COC), °C	135	190	-
Total base number (TBN), mg KOH/g	93	111	115
Calcium content, % wt.	3.05	3.32	3.67
Zinc content, % wt.	0.91	1.02	1.11
Phosphorus content, % wt.	0.82	0.92	1.02
Nitrogen content, % wt.	0.70	0.84	1.00
Condition of usage	Recommended solution temperature of package of additives in base oil is up to 70 °C. Any devices providing uniformity of stirring of package of additives in base oil can be used for dissolving. Shelf life at ambient temperature – 24 months.		
Safety requirements	Before usage the product please read material safety data sheet (MSDS) of the product.		